

AMBIENT CONTROL

Mechanical thermostat & hygrometers for temperature & humidity regulation in electrical enclosure, with DIN rail application

Model	NC - NO Mechanical Thermostat		Mechanical Hygrometers
	TRT-10A230V-NC	TRT-10A230V-NO	IGR35F
			
Rated Voltage (V.a.c) 50/60Hz	110-250		120-240
Rated Current (A)	10 (6*)		10-5
Contact Current carrying capacity (A)	15	15	-
Setting Range	-10 ~ +80 (°C)		10 ~ 90 (% RH)
Differential (referred to set point)	-3 (K)	+ 4 if A≤5 / + 7 if A>5 (K)	5 (% RH)
Accuracy (K)	± 3		-
Approvals	cURus		-
Operating Ambient Temperature (°C)	NIL		+10 ... + 60

ANTI CONDENSATION HEATERS

A variety of heaters for the thermo-regulation of electrical cabinets, connectable by cable or terminal block, with DIN rail fastening. The ventilated version enhances the heating power, up to thermal capacity of 400W.

Model	Heaters with cable	Heaters with terminal block	Ventilated heaters
	RAC-60	RACM-100	RACMV-250
			
Dimension H(mm) * L (mm)	102 * 61	167 * 61	197 * 61
Heating Power W*	60	100	250
External Surface (°C)	85	105	70

FAN FILTER

FF Series with an easy-to-mount tool-less fixing system with clips, optimized for 1 to 5mm thick enclosure.

Model	FF120A230UF		
Dimension (mm)	150 * 150		
Cut Out (mm)	125 * 125		
Voltage (V)	230 V.a.c		
Frequency (Hz)	50/60		
Rated Power (W)	18/17		
Max Air Flow (m³/h) **	45/50		
Rated Temp. Range (°c)	-10 ~ +55		
Approvals	CE cURus		

LED LAMPS

LED lamps with a metal fixing plate for an adjustable installation.

Model	CLG-L233		
Rated Voltage (V.a.c)	115 - 230		
Rated Frequency (Hz)	50 / 60		
Power (W)	3.0 / 3.0		
LED Number / Color	12		
Weight (kg)	White		
	0.203		