

Data cable feed-through

Data cable feed-through revos IT

2 bushings



3 bushings



4 bushings




Description	Type	Part No.	P.U.
Data cable feed-through revos IT			
2 bushings, Size 10	IT DKE 10	70.060.1028.0	10
3 bushings, Size 16	IT DKE 16	70.060.1628.0	10
4 bushings, Size 24	IT DKE 24	70.060.2428.0	5

Technical data	
Number of Bushings	
2 bushings	2
3 bushings	3
4 bushings	4
Cable diameter	
2 bushings	1 x 4.5 – 10 mm and 1 x 9 – 15 mm
3 bushings	2 x 4.5 – 10 mm and 1 x 9 – 15 mm
4 bushings	2 x 4.5 – 10 mm and 2 x 9 – 15 mm
Material	
Housing	Die cast aluminum
Gaskets	Neoprene (oil-resistant and anti-ageing)
Clamping screws	galvanically zinc-plated steel
Protection degree according to EN60529	IP 65
Temperature range	-40 – +100 °C


Description	Type	Part No.	P.U.
Accessories			
Rubber gasket for Connection range	2 mm – 10 mm	05.562.3183.0	20
Rubber gasket for Connection range	9 mm – 15 mm	05.562.3283.0	10
Housing Size 10			
without cover		70.320.1028.0	
Housing Size 16			
without cover		70.320.1628.0	
Housing Size 24			
without cover		70.320.2428.0	

Dimensions


2 bushings



3 bushings



4 bushings



D-Sub connectors

D-Sub connectors revos IT

Male



Female





Female





Description	Type	Part No.	P.U.
D-Sub connectors revos IT			
9-pole			
Male, Size 6	IT GOSL 1 M20 0.5 4 AU	Z7.415.0235.0	10
Female, Size 6	IT GUBL 1 0.5 4 AU	Z7.415.0010.0	10
D-Sub connectors revos IT			
2 x 9-pole			
Male, Size 6	IT GOSL 2 M20 0.5 4 AU	Z7.415.0335.0	10
Female, Size 6	IT GUBL 2 0.5 4 AU	Z7.415.0110.0	10
D-Sub connectors revos IT			
15-pole			
Male, Size 6	IT GOSL 3 M20 0.5 4 AU	Z7.415.1035.0	10
Female, Size 6	IT GUBL 3 0.5 4 AU	Z7.415.0810.0	10
D-Sub connectors revos IT			
2 x 15-pole			
Male, Size 6	IT GOSL 4 M20 0.5 4 AU	Z7.415.1135.0	10
Female, Size 6	IT GUBL 4 0.5 4 AU	Z7.415.0910.0	10
D-Sub connectors revos IT			
25-pole			
Male, Size 10	IT GOSL 5 M20 0.5 4 AU	Z7.415.1935.0	10
Female, Size 10	IT GUBL 5 0.5 4 AU	Z7.415.1610.0	10
D-Sub connectors revos IT			
15 + 25-pole			
Male, Size 10	IT GOSL 6 M20 0.5 4 AU	Z7.415.2135.0	10
Female, Size 10	IT GUBL 6 0.5 4 AU	Z7.415.1810.0	10
D-Sub connectors revos IT			
2 x 25-pole			
Male, Size 10	IT GOSL 7 M20 0.5 4 AU	Z7.415.2035.0	10
Female, Size 10	IT GUBL 7 0.5 4 AU	Z7.415.1710.0	10
D-Sub connectors revos IT			
37-pole			
Male, Size 16	IT GOSL 8 M20 0.5 4 AU	Z7.415.2635.0	10
Female, Size 16	IT GUBL 8 0.5 4 AU	Z7.415.2410.0	10
D-Sub connectors revos IT			
2 x 37-pole			
Male, Size 16	IT GOSL 9 M20 0.5 4 AU	Z7.415.2735.0	10
Female, Size 16	IT GUBL 9 0.5 4 AU	Z7.415.2510.0	10
D-Sub connectors revos IT			
50-pole			
Male, Size 16	IT GOSL 10 M20 0.5 4 AU	Z7.415.3335.0	10
Female, Size 16	IT GUBL 10 0.5 4 AU	Z7.415.3210.0	10
D-Sub connectors revos IT			
2 x 50-pole			
Male, Size 16	IT GOSL 11 M20 0.5 4 AU	Z7.415.3535.0	10
Female, Size 16	IT GUBL 11 0.5 4 AU	Z7.415.3410.0	10
Technical data			
Rated voltage	40 V		
Rated voltage according to UL/CSA	-		
Rated impulse voltage	1 kV		
Current carrying capability at 20 °C	5 A		
Degree of pollution	2		
Rated cross section			
EN 60947	Solder connection max. 0.5 mm ²		
UL	-		
CSA	-		
Contacts	hard gold plating over nickel plating		
Temperature range	-40 – +100 °C		

Dimensions

9-pole Size 6



25-pole Size 10



37-pole Size 16

